

CONCRETE T-LOK BARRIERS



Concrete T-Lok barriers are designed for traffic diversion and separation. The T-Lok precast Concrete Barrier has an Austroads Safety Barrier Acceptance Panel (ASBAP) approval to 80km/h as a temporary redirective longitudinal barrier.

This safety road barrier complies with AS/NZS 3845 and is MASH rated.

FEATURES

- Interconnecting T-Lok
- End protection available
- Rated to 80km/h
- Swift lift integrated lifter
- Anti-Gawk fencing available

CONCRETE BARRIER SPECIFICATIONS

Description	Dimensions	
	3.6m	5.4m
Height	810mm	810mm
Length	3.6m	5.4m
Weight Per Barrier	2556kg	3834kg
Weight Per Metre	710kg	710kg
Width (At Base)	610mm	610mm

ANTI-GAWK FENCING



ABSORB 350



SH 2000 WATER FILLED BARRIERS



Shore Hire offers the SH 2000 Water Filled Barrier. Whether you are looking for a traffic delineator for a slow speed work zone or pedestrian control, this barrier will meet your needs.

FEATURES

- Fast deployment
- Interlocked design to maximise transport & storage
- Built in locking system that requires no additional pins
- Perfect for multipurpose delineation requirements
- Provision for flashing lights & mesh fencing

WATER FILLED BARRIER SH 2000 SPECIFICATIONS

Description	Dimensions
Height	1000mm
Width	540mm
Length	2200mm
Coverage	2000mm
Empty Weight	37kg
Full Weight (Water)	262kg
Water Ballast	225L

TRITON BARRIERS



The Triton Barrier is an easy to use water filled portable plastic barrier with an internal steel frame for work zones. The Triton Barrier has a convenient modular design that consists of a series of interlocking 2m barrier sections. Triton Barrier provides approved work zone protection.

- Fast deployment – 183m per hour with just three workers
- Internal steel frame – no additional assembly required
- Effective in all weather conditions
- Quick release taps

TRITON BARRIER SPECIFICATIONS

Description	Dimensions
Length	2000mm
Width	500mm
Height	800mm
Empty Weight	65kg
Full Weight (Water)	615kg
Water Ballast	550L

Note: Specifications are approximate.